

T1	T2	T3	T4	T5	unit	full text	ctrl. no.	short text
30						<p>Polymer concrete jacking pipes</p> <p>polymer concrete jacking pipes acc. to DIN 54815, Part 1 and 2. dimensional tolerance acc. to ATV-A 125 pipes complete with guide ring, elastomeric sealing profile and pressure transfer ring</p> <p>manufacturer: Meyer Rohr + Schacht GmbH, Otto-Brenner-Str. 5 21337 Lüneburg, Tel.: 04131/953-0, Fax: 953-255 or equivalent</p> <p>circular cross-section kite-shaped cross-section</p> <p>pipe connection with jacking coupling stainless steel guide ring for pipe connection, mat no. 1.4571 weathering resistant steel guide ring for pipe connection, mat. no. 1.8963</p> <p>standard length 1.0 m standard length 2.0 m standard length 3.0 m</p>		
	1							
	2							
		1						
		2						
		3						
			1					
			2					
			3					
		01			m	DN 150		DN 150
		02			m	DN 200		DN 200
		03			m	DN 250		DN 250
		04			m	DN 300		DN 300
		05			m	DN 400		DN 400
		06			m	DN 500		DN 500
		07			m	DN 600		DN 600
		08			m	DN 700		DN 700
		09			m	DN 800		DN 800
		10			m	DN 900		DN 900
		11			m	DN 1000		DN 1000
		12			m	DN 1200		DN 1200
		13			m	DN 1400		DN 1400
		14			m	DN 1500		DN 1500
		15			m	DN 1600		DN 1600
		16			m	DN 1800		DN 1800

T1	T2	T3	T4	T5	unit	full text	ctrl. no.	short text
31						additional equipment flexible connections, fitting lengths, short pipes in standard length short standard length, complete with guide ring, elastomeric sealing profile and pressure transfer ring on one pipe face		
	01				run.m	DN 150		DN 150
	02				run.m	DN 200		DN 200
	03				run.m	DN 250		DN 250
	04				run.m	DN 300		DN 300
	05				run.m	DN 400		DN 400
	06				run.m	DN 500		DN 500
	07				run.m	DN 600		DN 600
	08				run.m	DN 700		DN 700
	09				run.m	DN 800		DN 800
	10				run.m	DN 900		DN 900
	11				run.m	DN 1000		DN 1000
	12				run.m	DN 1200		DN 1200
	13				run.m	DN 1400		DN 1400
	14				run.m	DN 1500		DN 1500
	15				run.m	DN 1600		DN 1600
	16				run.m	DN 1800		DN 1800